

45° Street Elbow

FTG x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CarbonPress® 45° Street Elbow FTG x P is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

CarbonPress® Certifications

IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).


CarbonPress® Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.


45° Street Elbow

FTG x P

Item Number			Nominal Size 1	A (in)	L (in)	L1 (in)
EPDM	HNBR	FKM				
MB90585	MB90586	MB90587	½"	0.87	1.89	2.17
MB90590	MB90591	MB90592	¾"	1.00	2.19	2.42
MB90595	MB90596	MB90597	1"	1.16	2.52	3.07
MB90600	MB90601	MB90602	1¼"	1.43	3.23	3.43
MB90605	MB90606	MB90607	1½"	1.54	3.41	3.74
MB90610	MB90611	MB90612	2"	1.87	3.80	3.94



XL 45° Street ElbowFTG x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CarbonPress® XL 45° Street Elbow FTG x P is available in sizes 2½" – 4" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:
Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

CarbonPress® Certifications
IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress® Codes and Standards
IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

XL 45° Street Elbow			FTG x P			
Item Number			Nominal Size 1	A (in)	L (in)	L1 (in)
EPDM	HNBR	FKM				
MB90615	MB90616	MB90617	2½"	2.05	3.92	4.23
MB90620	MB90621	MB90622	3"	2.40	4.69	4.57
MB90625	MB90626	MB90627	4"	2.99	6.14	5.94

