

Cap		P
	Job Name	<input type="text"/>
	Job Location	<input type="text"/>
	P.O.#	<input type="text"/>
	Engineer	<input type="text"/>
	Contractor	<input type="text"/>
	Wholesaler	<input type="text"/>
	Merit Associate	<input type="text"/>

**CarbonPress® Cap** is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**CarbonPress® Operational Parameters:**

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.


**CarbonPress® Certifications**

IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

**CarbonPress® Codes and Standards**

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Cap					P
Item Number			Nominal Size 1	A (in)	L (in)
EPDM	HNBR	FKM			
MB90630	MB90631	MB90632	½"	1.02	1.81
MB90635	MB90636	MB90637	¾"	1.18	2.01
MB90640	MB90641	MB90642	1"	1.36	2.19
MB90645	MB90646	MB90647	1¼"	1.80	2.83
MB90650	MB90651	MB90652	1½"	1.85	2.91
MB90655	MB90656	MB90657	2"	1.93	3.01



XL Cap

P



Job Name	<input type="text"/>
Job Location	<input type="text"/>
P.O.#	<input type="text"/>
Engineer	<input type="text"/>
Contractor	<input type="text"/>
Wholesaler	<input type="text"/>
Merit Associate	<input type="text"/>

- CarbonPress® XL Cap** is available in sizes 2½" – 4" with an EPDM, HNBR or FKM sealing element.
- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
  - **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
  - **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
  - **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
  - **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**CarbonPress® Operational Parameters:**  
Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**CarbonPress® Certifications**  
IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

**CarbonPress® Codes and Standards**  
IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

XL Cap

P

Item Number			Nominal Size 1	A (in)	L (in)
EPDM	HNBR	FKM			
MB90660	MB90661	MB90662	2½"	1.87	3.60
MB90665	MB90666	MB90667	3"	2.30	4.21
MB90670	MB90671	MB90672	4"	3.13	5.39

