

**Carbon Extended Coupling w/o Stop**

P x P



**Job Name**

**Job Location**

**P.O.#**

**Engineer**

**Contractor**

**Wholesaler**

**Merit Associate**

**MeritPress™ - Carbon Extended Coupling w/o Stop P x P** is available in sizes ½" – 2" with an EPDM, HNBR and FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™:** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the Visual Indicator Press Ring (VIPR)™, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**MeritPress™ - Carbon Press Operational Parameters**

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**MeritPress™ - Carbon Press Certifications**

IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR), and UL 213 and FM 1920 (EPDM & FKM).

**MeritPress™ - Carbon Press Codes and Standards**

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

**Carbon Extended Coupling w/o Stop**

P x P

Item Number			Nominal Size 1	L (in)
EPDM	HNBR	FKM		
MB90090	MB90091	MB90092	½"	3.82
MB90095	MB90096	MB90097	¾"	4.00
MB90100	MB90101	MB90102	1"	4.37
MB90105	MB90106	MB90107	1¼"	5.31
MB90110	MB90111	MB90112	1½"	5.43
MB90115	MB90116	MB90117	2"	5.63

