

Extended Coupling w/o Stop

P x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

- CarbonPress® Extended Coupling w/o Stop P x P** is available in sizes ½" – 2" with an EPDM, HNBR and FKM sealing element.
- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
 - **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
 - **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
 - **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
 - **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

CarbonPress® Operational Parameters:

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

CarbonPress® Certifications

IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

CarbonPress® Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Extended Coupling w/o Stop

P x P

Item Number			Nominal Size 1	L (in)
EPDM	HNBR	FKM		
MB90090	MB90091	MB90092	½"	3.82
MB90095	MB90096	MB90097	¾"	4.00
MB90100	MB90101	MB90102	1"	4.37
MB90105	MB90106	MB90107	1¼"	5.31
MB90110	MB90111	MB90112	1½"	5.43
MB90115	MB90116	MB90117	2"	5.63

