

**Female Adapter**

**P x FPT**



**Job Name**

**Job Location**

**P.O.#**

**Engineer**

**Contractor**

**Wholesaler**

**Merit Associate**

**Female Adapter**

**P x FPT**

Item Number			Nominal Size		A (in)	L (in)
EPDM	HNBR	FKM	Size 1	Size 2		
MB90720	MB90721	MB90722	½"	½"	0.83	2.52
MB90725	MB90726	MB90737	¾"	½"	0.98	2.83
MB90730	MB90731	MB90727	¾"	¾"	0.87	2.72
MB90735	MB90736	MB90747	1"	½"	1.46	3.48
MB90740	MB90741	MB90738	1"	¾"	1.08	3.11
MB90745	MB90746	MB90742	1"	1"	0.91	3.05
MB90750	MB90751	MB90767	1¼"	½"	1.67	4.13
MB90755	MB90756	MB90752	1¼"	¾"	1.67	4.13
MB90760	MB90761	MB90757	1¼"	1"	1.16	3.76
MB90765	MB90766	MB90762	1¼"	1¼"	1.06	3.72
MB90770	MB90771	MB90792	1½"	½"	1.69	4.21
MB90775	MB90776	MB90772	1½"	¾"	1.69	4.21
MB90780	MB90781	MB90777	1½"	1"	1.73	4.37
MB90785	MB90786	MB90782	1½"	1¼"	1.18	3.90
MB90790	MB90791	MB90787	1½"	1½"	1.06	3.90
MB90795	MB90796	MB90822	2"	½"	1.71	4.31
MB90800	MB90801	MB90797	2"	¾"	1.71	4.31
MB90805	MB90806	MB90802	2"	1"	1.75	4.47
MB90810	MB90811	MB90807	2"	1¼"	1.77	4.57
MB90815	MB90816	MB90812	2"	1½"	1.46	4.37
MB90820	MB90821	MB90817	2"	2"	1.20	4.15

**CarbonPress® Female Adapter P x FPT** is available in sizes ½" – 2" with an EPDM, HNBR and FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**CarbonPress® Operational Parameters:**


Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**CarbonPress® Certifications**

IAPMO Z 1117 (EPDM and FKM). IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

**CarbonPress® Codes and Standards**

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.



XL Female Adapter

P x FPT



Job Name	<input type="text"/>
Job Location	<input type="text"/>
P.O.#	<input type="text"/>
Engineer	<input type="text"/>
Contractor	<input type="text"/>
Wholesaler	<input type="text"/>
Merit Associate	<input type="text"/>

CarbonPress® XL Female Adapter P x FPT is available in sizes 2½" – 4" with an EPDM, HNBR and FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®):** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

**CarbonPress® Operational Parameters:**  
Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

**CarbonPress® Certifications**  
IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR).

**CarbonPress® Codes and Standards**  
IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

XL Female Adapter

P x FPT

Item Number			Nominal Size		A (in)	L (in)
EPDM	HNBR	FKM	Size 1	Size 2		
MB90825	MB90826	MB90827	2½"	2½"	1.06	4.00
MB90830	MB90831	MB90832	3"	3"	1.20	4.65
MB90835	MB90836	MB90837	4"	4"	1.32	5.71

