

Carbon Female Union

P x FPT



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

MeritPress™ - Carbon Female Union P x FPT is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring (VIPR)™:** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP):** in addition to the Visual Indicator Press Ring (VIPR)™, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Surface Protection:** Corrosion Resistant Zn-Ni Plating.
- **Grab Ring:** Deforms and Grips Outside Diameter of Pipe.
- **Applications:** Hydronic Heating, the Conveyance of Fluids, Gases, Oils, and Low-Pressure Steam.

MeritPress™ - Carbon Press Operational Parameters

Working pressure range from full vacuum to 250 psi (17.2 bar) for water, 125 psi (8.6 bar) for gas, and 200 psi (13.7 bar) for industrial applications.

MeritPress™ - Carbon Press Certifications

IAPMO Z 1117 (EPDM and FKM), IAPMO/ANSI LC 4/CSA 6.32 (HNBR), and UL 213 and FM 1920 (EPDM & FKM).

MeritPress™ - Carbon Press Codes and Standards

IAPMO Z 1117, IAPMO/ANSI LC 4/CSA 6.32, ASME B31.1, B31.3, B31.9, CSA B149.1, UPC, and UMC.

Carbon Female Union

P x FPT

Item Number			Nominal Size		A (in)	A1 (in)	L (in)
EPDM	HNBR	FKM	Size 1	Size 2			
MB90936	MB90955	MB90956	½"	½"	1.52	0.59	2.48
MB90939	MB90958	MB90959	¾"	¾"	1.75	0.67	2.78
MB90942	MB90961	MB90962	1"	1"	1.85	0.71	3.09
MB90945	MB90964	MB90965	1¼"	1¼"	2.42	0.71	4.09
MB90948	MB90967	MB90968	1½"	1½"	2.48	0.87	4.27
MB90951	MB90970	MB90971	2"	2"	2.93	1.04	4.92

