

Standard Plumbing Straight Tube

- 1/4" 6" Nominal Size Type L, K & M
- NSF 61 Compliant
- ASTM B75
- Available in Soft, Hard or Half-Hard Lengths 10' or 20'

ACR Straight Refrigeration Tube

- 1/4" 4" Nominal Size Type L & K
- ASTM B280
- Available in Hard Lengths 10' or 20'
- Cleaned & Capped

DWV Straight Tube

- 1-1/4" 4" Nominal Size
- Available in 20' Lengths
- ASTM B306

ACR Refrigeration Coils

- 1/4" 1-5/8" OD Size Type L & K
- ASTM B280
- Available in 15', 50', 100' Coils
- Cleaned & Capped
- Not Nitrogen Charged



Advantages of Copper

- Corrosion-resistant Recyclable
- Ease of Installation
 Lightweight
- Ductile
- Reacts Well to Water



800.726.9800

www.meritbrass.com/en/contact-us

CONTACT US



Nominal or Standard Size (In.)		TYPE L	TYPE K	TYPE M
	Nominal Dimensions (In.)			
	Outside Diameter	Wall Thickness	Wall Thickness	Wall Thickness
1/4	0.375	0.030	0.035	N/A
3/8	0.500	0.035	0.049	0.025
1/2	0.625	0.040	0.049	0.028
5/8	0.750	0.042	0.049	N/A
3/4	0.875	0.045	0.065	0.032
1	1.125	0.050	0.065	0.035
1-1/4	1.375	0.055	0.065	0.042
1-1/2	1.625	0.060	0.072	0.049
2	2.125	0.070	0.083	0.058
2-1/2	2.625	0.080	0.095	0.065
3	3.125	0.090	0.109	0.072
3-1/2	3.625	0.100	0.120	0.083
4	4.125	0.110	0.134	0.095
5	5.125	0.125	0.160	0.109
6	6.125	0.140	0.192	0.122

Indent Order Requirements

Order Minimum: 22,500 LB.
Average Delivery: 130-Days

• Terms: Net 30-Days

• Merit Stenciling Available Upon Request

Price Valid for 24-Hours | Price at Time of Order









