


XL 45° Street Elbow



FTG x P

Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CopperPress® Large Diameter 45° Street Elbow is available in sizes 2½" – 4" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

XL 45° Street Elbow				FTG x P
Item Number	D1 (in)	L (in)	A (in)	L2 (in)
EPDM				
MB22200	2½"	3.15	1.42	3.39
MB22210	3"	3.70	1.69	3.98
MB22220	4"	4.80	2.40	5.08

