


XL Bushing Reducer	FTG x P
	Job Name <input type="text"/>
	Job Location <input type="text"/>
	P.O.# <input type="text"/>
	Engineer <input type="text"/>
	Contractor <input type="text"/>
	Wholesaler <input type="text"/>
	Merit Associate <input type="text"/>
<p>CopperPress® Large Diameter Bushing Reducer FTG x P is available in sizes 2½" x 1" – 4" x 3" with an EPDM sealing element.</p> <ul style="list-style-type: none">• FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections.• Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.• Applications: HVAC, plumbing, municipal, mechanical and industrial applications.	

XL Bushing Reducer					FTG x P
Item Number	D1 (in)	D2 (in)	L (in)	A (in)	
EPDM					
MB22400	2½"	1"	4.25	3.31	
MB22410	2½"	1¼"	4.06	2.91	
MB22420	2½"	1½"	4.29	2.83	
MB22430	2½"	2"	4.25	2.64	
MB22440	3"	1¼"	4.53	3.39	
MB22450	3"	1½"	4.92	3.46	
MB22460	3"	2"	4.80	3.19	
MB22470	3"	2½"	4.53	2.80	
MB22480	4"	2"	6.18	4.57	
MB22490	4"	2½"	5.79	4.06	
MB22500	4"	3"	5.71	3.70	

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

