


XL Cap		P
	<div>Job Name</div> <div>Job Location</div> <div>P.O.#</div> <div>Engineer</div> <div>Contractor</div> <div>Wholesaler</div> <div>Merit Associate</div>	
	<p><b>CopperPress® Large Diameter Cap</b> is available in sizes 2½" – 4" with an EPDM sealing element.</p> <ul style="list-style-type: none"><li>• <b>FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)</b> - facilitates immediate identification of un-pressed connections.</li><li>• <b>Leak Before Press (LBP)</b> - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.</li><li>• <b>Applications:</b> HVAC, plumbing, municipal, mechanical and industrial applications.</li></ul> <p><b>CopperPress® Operational Parameters:</b> EPDM working pressure range from full vacuum to 300 psi for water.</p> <p><b>CopperPress® Fitting Certifications</b> ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p><b>CopperPress® Codes and Standards</b> ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC &amp; CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>	

XL Cap				P
Item Number	D1 (in)	L (in)	A (in)	
EPDM				
MB23110	2½"	2.17	0.43	
MB23120	3"	2.44	0.43	
MB23130	4"	2.87	0.47	

