

XL Reducing Tee (P x FPT)	P x P x FPT
	<div><div>Job Name</div><div>Job Location</div><div>P.O.#</div><div>Engineer</div><div>Contractor</div><div>Wholesaler</div><div>Merit Associate</div></div>
<p>CopperPress® Large Diameter Reducing Tee P x P x FPT is available in sizes 2½" x ¾" FPT – 4" x 2" FPT with an EPDM sealing element.</p> <ul style="list-style-type: none">• FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections.• Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.• Applications: HVAC, plumbing, municipal, mechanical and industrial applications. <p>CopperPress® Operational Parameters: EPDM working pressure range from full vacuum to 300 psi for water.</p> <p>CopperPress® Fitting Certifications ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p>CopperPress® Codes and Standards ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>	

XL Reducing Tee (P x FPT)			P x P x FPT			
Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
EPDM						
MB42000	2½"	¾" FPT	3.25	1.52	3.50	2.87
MB42010	2½"	2" FPT	3.25	1.52	3.43	2.48
MB42030	3"	¾" FPT	3.64	1.63	4.02	3.39
MB42040	3"	2" FPT	3.64	1.63	3.58	2.64
MB42050	4"	¾" FPT	4.02	1.61	3.90	3.27
MB42060	4"	2" FPT	4.02	1.61	3.70	2.76

