

## 45° Street Elbow

FTG x P



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

**CopperPress® Small Diameter 45° Street Elbow** is available in sizes 1/2" – 2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

### CopperPress® Operational Parameters:

EPDM working pressure range from full vacuum to 300 psi for water.

### CopperPress® Fitting Certifications

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

### CopperPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

## 45° Street Elbow

FTG x P

Item Number	D1 (in)	L (in)	A (in)	L2 (in)
EPDM				
MB11590	1/2"	1.10	0.30	1.22
MB11600	3/4"	1.40	0.45	1.46
MB11610	1"	1.52	0.57	1.57
MB11620	1 1/4"	1.97	0.83	1.94
MB11630	1 1/2"	2.30	0.85	2.36
MB11640	2"	2.44	0.83	2.76

