


90° Elbow



P x P

Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CopperPress® Small Diameter 90° Elbow P x P is available in sizes ½" – 2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

90° Elbow		P x P	
Item Number	D1 (in)	L (in)	A (in)
EPDM			
MB11230	½"	1.56	0.75
MB11240	¾"	1.97	1.02
MB11250	1"	2.24	1.30
MB11260	1¼"	2.64	1.50
MB11270	1½"	3.23	1.77
MB11280	2"	3.98	2.36

