


90° Reducing Elbow



Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CopperPress® Small Diameter 90° Reducing Elbow P x P is available in sizes 3/4" x 1/2" – 1" x 3/4" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

90° Reducing Elbow						P x P
Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
EPDM						
MB24560	3/4"	1/2"	1.83	0.89	1.69	0.89
MB24570	1"	3/4"	2.30	1.36	2.01	1.06

