


90° Street Elbow



FTG x P

Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CopperPress® Small Diameter 90° Street Elbow FTG X P is available in sizes ½" – 2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

| 90° Street Elbow | | | | FTG x P |
|------------------|---------|---------|--------|---------|
| Item Number | D1 (in) | L1 (in) | A (in) | L2 (in) |
| EPDM | | | | |
| MB11350 | ½" | 1.56 | 0.75 | 1.73 |
| MB11360 | ¾" | 2.03 | 1.08 | 2.13 |
| MB11370 | 1" | 2.24 | 1.30 | 2.36 |
| MB11380 | 1¼" | 2.64 | 1.50 | 2.93 |
| MB11390 | 1½" | 3.23 | 1.77 | 3.54 |
| MB11400 | 2" | 3.98 | 2.17 | 4.29 |

