


Bushing Reducer		FTG x P	
	Job Name	<input type="text"/>	
	Job Location	<input type="text"/>	
	P.O.#	<input type="text"/>	
	Engineer	<input type="text"/>	
	Contractor	<input type="text"/>	
	Wholesaler	<input type="text"/>	
	Merit Associate	<input type="text"/>	

CopperPress® Small Diameter Bushing Reducer FTG x P is available in sizes 3/4" x 1/2" – 2" x 1 1/2" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

Bushing Reducer				FTG x P
Item Number	D1 (in)	D2 (in)	L (in)	A (in)
EPDM				
MB12530	3/4"	1/2"	2.15	1.34
MB12540	1"	1/2"	2.32	1.52
MB12550	1"	3/4"	2.24	1.30
MB12560	1 1/4"	1/2"	2.64	1.83
MB12570	1 1/4"	3/4"	2.64	1.69
MB12580	1 1/4"	1"	2.52	1.57
MB12585	1 1/2"	1/2"	3.03	2.22
MB12590	1 1/2"	3/4"	3.11	2.17
MB12600	1 1/2"	1"	2.95	2.01
MB12610	1 1/2"	1 1/4"	3.03	1.89
MB12613	2"	1/2"	3.66	2.85
MB12617	2"	3/4"	3.74	2.80
MB12620	2"	1"	3.54	2.60
MB12630	2"	1 1/4"	3.58	2.44
MB12640	2"	1 1/2"	3.70	2.24

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

