


Cap	P
	<div><div>Job Name</div><div>Job Location</div><div>P.O.#</div><div>Engineer</div><div>Contractor</div><div>Wholesaler</div><div>Merit Associate</div></div>
<p>CopperPress® Small Diameter Cap is available in sizes ½" – 2" with an EPDM sealing element.</p> <ul style="list-style-type: none">• FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections.• Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.• Applications: HVAC, plumbing, municipal, mechanical and industrial applications. <p>CopperPress® Operational Parameters: EPDM working pressure range from full vacuum to 300 psi for water.</p> <p>CopperPress® Fitting Certifications ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p>CopperPress® Codes and Standards ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>	

Cap				P
Item Number	D1 (in)	L (in)	A (in)	
EPDM				
MB13110	½"	0.94	0.14	
MB13120	¾"	1.06	0.12	
MB13140	1"	1.06	0.12	
MB13150	1¼"	1.26	0.12	
MB13160	1½"	1.69	0.24	
MB13170	2"	1.85	0.24	

