


Coupling with Stop		P x P
	<div>Job Name</div> <div>Job Location</div> <div>P.O.#</div> <div>Engineer</div> <div>Contractor</div> <div>Wholesaler</div> <div>Merit Associate</div>	
	<p>CopperPress® Small Diameter Coupling with Stop P x P is available in sizes ½" – 2" with an EPDM sealing element.</p> <ul style="list-style-type: none">• FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections.• Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.• Applications: HVAC, plumbing, municipal, mechanical and industrial applications. <p>CopperPress® Operational Parameters: EPDM working pressure range from full vacuum to 300 psi for water.</p> <p>CopperPress® Fitting Certifications ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p>CopperPress® Codes and Standards ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>	

Coupling with Stop		P x P	
Item Number	D1 (in)	L (in)	A (in)
EPDM			
MB12230	½"	1.61	0.12
MB12240	¾"	2.05	0.16
MB12250	1"	2.05	0.16
MB12260	1¼"	2.44	0.16
MB12270	1½"	3.03	0.16
MB12280	2"	3.35	0.16

