


Crossover



P x P

Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

**CopperPress® Small Diameter Crossover** is available in sizes 1/2" – 3/4" with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

**CopperPress® Operational Parameters:**  
EPDM working pressure range from full vacuum to 300 psi for water.

**CopperPress® Fitting Certifications**  
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

**CopperPress® Codes and Standards**  
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

Crossover				P x P
Item Number	D1 (in)	D2 (in)	L (in)	A (in)
EPDM				
MB23140	1/2"	5.20	3.58	0.77
MB23150	3/4"	6.34	4.45	0.91

