

Extended Coupling w/o Stop		P x P
	Job Name <input type="text"/>	
	Job Location <input type="text"/>	
	P.O.# <input type="text"/>	
	Engineer <input type="text"/>	
	Contractor <input type="text"/>	
	Wholesaler <input type="text"/>	
	Merit Associate <input type="text"/>	
<p>CopperPress® Small Diameter Extended Coupling w/o Stop P x P is available in sizes ½" – 2" with an EPDM sealing element.</p> <ul style="list-style-type: none"> • FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections. • Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed. • Applications: HVAC, plumbing, municipal, mechanical and industrial applications. <p>CopperPress® Operational Parameters: EPDM working pressure range from full vacuum to 300 psi for water.</p> <p>CopperPress® Fitting Certifications ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p>CopperPress® Codes and Standards ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>		

Extended Coupling w/o Stop		P x P
Item Number	D1 (in)	L (in)
EPDM		
MB12350	½"	2.99
MB12360	¾"	3.50
MB12370	1"	3.74
MB12380	1¼"	4.13
MB12390	1½"	4.72
MB12400	2"	5.31

