


Flange Adapter	P x Flange
	<div><div>Job Name</div><div>Job Location</div><div>P.O.#</div><div>Engineer</div><div>Contractor</div><div>Wholesaler</div><div>Merit Associate</div></div>
<p>CopperPress® Flange Adapter is available in sizes 1" – 4" with an EPDM sealing element.</p> <ul style="list-style-type: none">• FIRST TO MARKET Visual Indicator Press Ring® (VIPR®) - facilitates immediate identification of un-pressed connections.• Leak Before Press (LBP) - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.• Applications: HVAC, plumbing, municipal, mechanical and industrial applications. <p>CopperPress® Operational Parameters: EPDM working pressure range from full vacuum to 300 psi for water.</p> <p>CopperPress® Fitting Certifications ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.</p> <p>CopperPress® Codes and Standards ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.</p>	

Flange Adapter					P x Flange			
Item Number	D1 (in)	L (in)	A (in)	b (in)	D (in)	K (in)	d (in)	n (in)
EPDM								
MB60000	1"	2.28	1.34	0.63	4.33	3.11	0.63	4
MB60010	1¼"	2.28	1.14	0.63	4.53	3.50	0.63	4
MB60020	1½"	2.60	1.14	0.63	4.92	3.86	0.63	4
MB60030	2"	2.76	1.14	0.63	5.91	4.76	0.75	4
MB60040	2½"	2.83	1.10	0.69	7.09	5.51	0.75	4
MB60050	3"	3.25	1.34	0.81	7.48	5.98	0.75	4
MB60060	4"	3.74	1.34	0.89	9.06	7.52	0.75	8

