

Female Street Adapter		FTG x FPT	
	Job Name	<input type="text"/>	
	Job Location	<input type="text"/>	
	P.O.#	<input type="text"/>	
	Engineer	<input type="text"/>	
	Contractor	<input type="text"/>	
	Wholesaler	<input type="text"/>	
	Merit Associate	<input type="text"/>	

CopperPress® Small Diameter Female Street Adapter is available in sizes 1/2" x 3/8" FPT – 2" x 2" FPT with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

Female Street Adapter				FTG x FPT
Item Number	D1 (in)	D2 (in)	L (in)	A (in)
EPDM				
MB32000	1/2"	3/8" FPT	1.57	1.10
MB32010	1/2"	1/2" FPT	1.73	1.18
MB32020	1/2"	3/4" FPT	1.93	1.30
MB32030	3/4"	1/2" FPT	1.73	1.18
MB32040	3/4"	3/4" FPT	1.93	1.30
MB32050	1"	1" FPT	1.81	1.26
MB32060	1"	1/2" FPT	1.93	1.30
MB32065	1"	3/4" FPT	1.99	1.28
MB32070	1 1/4"	1/2" FPT	2.03	1.48
MB32080	1 1/4"	1 1/4" FPT	2.32	1.54
MB32090	1 1/2"	1 1/2" FPT	2.58	1.75
MB32100	2"	2" FPT	3.07	2.09

CopperPress® Operational Parameters:

EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

