


Female Union



P x FPT

Job Name

Job Location

P.O.#

Engineer

Contractor

Wholesaler

Merit Associate

CopperPress® Small Diameter Female Union is available in sizes ½" x ½" FPT – 2" x 2" FPT with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:
EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications
ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards
ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

Female Union				P x FPT
Item Number	D1 (in)	D2 (in)	L (in)	A (in)
EPDM				
MB35000	½"	½" FPT	1.99	0.67
MB35010	¾"	¾" FPT	2.15	0.61
MB35020	1"	1" FPT	2.26	0.65
MB35030	1¼"	1¼" FPT	2.93	1.00
MB35040	1½"	1½" FPT	2.91	0.67
MB35050	2"	2" FPT	3.31	0.75

