

Male Adapter	P x MPT
	Job Name <input type="text"/> Job Location <input type="text"/> P.O.# <input type="text"/> Engineer <input type="text"/> Contractor <input type="text"/> Wholesaler <input type="text"/> Merit Associate <input type="text"/>

Male Adapter		P x MPT		
Item Number	D1 (in)	D2 (in)	L (in)	A (in)
EPDM				
MB23250	½"	¾" MPT	1.65	0.85
MB23260	½"	½" MPT	1.69	0.89
MB23270	½"	¾" MPT	1.77	1.10
MB23280	¾"	½" MPT	2.05	0.94
MB23290	¾"	¾" MPT	1.89	0.94
MB23300	¾"	1" MPT	2.05	1.10
MB23310	1"	½" MPT	2.13	1.18
MB23320	1"	¾" MPT	1.93	0.98
MB23330	1"	1" MPT	1.93	1.22
MB23340	1"	1¼" MPT	2.09	1.14
MB23350	1¼"	1" MPT	2.20	1.06
MB23360	1¼"	1¼" MPT	2.20	1.06
MB23370	1¼"	1½" MPT	2.28	1.14
MB23380	1½"	1¼" MPT	2.70	1.24
MB23390	1½"	1½" MPT	2.64	1.18
MB23400	1½"	2" MPT	2.64	1.18
MB23410	2"	1½" MPT	2.83	1.22
MB23420	2"	2" MPT	2.80	1.46

CopperPress® Small Diameter Male Adapter is available in sizes ½" x ¾" MPT – 2" x 2" MPT with an EPDM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** facilitates immediate identification of un-pressed connections.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical and industrial applications.

CopperPress® Operational Parameters:

EPDM working pressure range from full vacuum to 300 psi for water.

CopperPress® Fitting Certifications

ICC-ES LC1002, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, IAPMO Z 1117.

CopperPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing and Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code, Massachusetts State Building Code 780 CMR Ninth Edition: Chapter 28.

