



BACKUP FLANGES

DUCTILE IRON

Size Range: 1/2" - 12"

GALVANIZED DUCTILE IRON

Size Range: 1" - 12"

MANUFACTURED TO ASTM A536 GRADES 65-45-12 STANDARD

LOW CARBON CONTENT & CORROSION RESISTANT





www.meritbrass.com www.mbwebxpress.com contactus@meritbrass.com

Merit Brass Headquarters Has An ISO 9001:2015 Registered Quality Management System



Pipe Nipples			
Red Brass (Standard/Extra Heavy) ASTM B687**		1/8" – 6"	
Chrome Plated Red Brass ASTM B687**		1/8" – 6"	
Stainless Steel (304/L & 316/L) ASTM A733	Schedule 40 Welded	1/8" – 8"	
	Schedule 40 & 80 Seamless	1/8" – 3"	
Aluminum (6061-40)		1/8" – 4"	

Pipe		
Red Brass ASTM B43**	Standard H58 Hard Temper	1/8" – 6"
	Standard 061 Annealed Temper	1/8" – 4"
	Extra Heavy H58 Hard Temper	1/8" – 4"
	Chrome Plated H58 Hard Temper	1/4" - 4"
Stainless Steel (304/L & 316/L) ASTM A312/SA312	Welded Schedule 10	1/2" – 12"
	Schedule 40 Welded	1/8" – 12"
	Schedule 80 Welded	1/8" – 4"
	Schedule 40 Seamless	1/8" – 4"
	Schedule 80 Seamless	1/8" – 4"
Aluminum ASTM B241 (6061-T6) - Standard		1/8" – 6"

	Tubing	
Stainless Steel (304/L & 316/L) (0.035,	Seamless (ASTM A213/A269)	1/4" – 1"
0.049, 0.065, 0.080, 0.095, 0.109 Walls)	Welded (ASTM A249/A269)	1/4" – 1"

Syphons	
Brass**	1/4"
Stainless Steel (304/L & 316/L)	1/4"

Таре	
Stainless Steel PTFE Thread Tape	1/2" & 3/4"

Valves		
Stainless Steel - K Series	1/2" – 6"	
Stainless Steel - V Series	1/2" – 3"	
Brass - Leaded* & Lead-Free**	1/4" – 4"	
Instrumentation	1/4" – 1/2"	

Tube Fittings	
Stainless Steel	1/8" – 1"

- Pipe Nipple Threading Capabilities
- » NPT (National Pipe Taper)
- » NPTF (National Pipe Taper Fuel & Oil)
- » NPSL (National Pipe Straight Locknut)
- » NPSM (National Pipe Straight Mechanical)
- » NPSH (National Pipe Straight Hose)
- » BSPT (British Standard Pipe Taper)

Pipe/Pipe Nipple Manufacturing Capabilities

- » Plain Roller Cut
- » Plain Square Cut
- » Plain Ream & Chamfer
- » Groove (Roll or Cut)
- » Per Print Bending (1/8" 1" Diameter)
- » Per Print O.D. & I.D. Machining

		Fittin	gs		
	Domestic	Domestic (125LB & 250LB)			1/8" – 6"
Brass Threaded ASTM B584 Leaded* Lead-Free**	Import (12	Import (125LB & 250LB)			1/8" – 4"
	Chrome P	Chrome Plated (125LB)			1/8" – 2"
Brass Barstock	Domestic	Domestic (125LB) – Leaded* & Lead-Free**			1/8" – 3/4"
	Cast 150LE	Cast 150LB (Standard) (AISI 304 & 316)			1/8" – 4"
	Cast 150LB MSS SP-114		SS Threaded		1/8" – 4"
			Socket Weld		1/2" – 2"
	Barstock 1	000lb A	.stm	A182 or A479	1/8" – 3"
Stainless Steel (304 & 316)	3000LB (Th	readed	& So	ocket Weld) ASTM A182	1/8" – 3"
	Buttweld (Schedu	les 1	0 & 40) ASTM A403	1/2" - 12"
	MSS Type		Sc	hedule 10	1/8" – 3"
	Stub Ends A403	ASIM	Sc	hedule 40 (Type A Only)	1/2" - 8"
	2000LB Thr	eaded			1/4" – 2"
Carbon Steel Forged A105-N	3000LB Thr	eaded			1/8" – 3"
	3000LB Soc	cket We	ld		1/2" - 3"
		Outle	ets		
Threaded 1/8" - 4"					
Stainless Steel (304/L & 316/L)		Socket Weld		1/2" - 4"	
		Buttweld (Schedule 40)		1/2" - 4"	
		Threaded		1/2" - 4"	
Carbon Steel Forged A105-1	٧	Socket Weld		1/2" - 4"	
		Buttweld (Schedule 40)		1/2" - 4"	
		Flang	ges		
Brass - Import & Domestic Leaded* & Lead-Free**	Companior ASTM B584	n (Threa	ded	(150LB & 300LB)	1/2" – 6"
	ANSI 150LB & 300LB (304/L & 316/L) ASTM A182		1/2" – 12"		
	MSS 150LB (304 & 316) ASTM A351			1/2" - 10"	
Stainless Steel		Plate (304/L & 316/L)		Tube OD Slip On	1-1/2" – 12"
	Plate (304/L (150LB)			Blind	1" – 12"
	/			IPS Slip On	1" – 12"
Ductile Iron Backup ASTM A536 & Galvanized 1/2" - 12"				1/2" – 12"	
Engineered Products					

Engineered Products		
	Fittings 1/2" – 4" and Valves 1/2" – 2" (EPDM)	
	Fittings 1/2" – 4" (HNBR, EPDM & FKM)	
	Fittings and Valves 1/2" – 2" (HNBR, EPDM & FKM)	
	Fittings 1/2" – 4" and Valves 1/2" – 2" (EPDM)	

Every precaution has been taken in preparing this sheet. Merit Brass Company cannot be held responsible for omissions or typographical errors.

* 🛦 WARNING: This product can expose you to Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <u>www.P65Warnings.ca.gov</u>. Leaded product is not for use in potable water.

** Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <=0.25 weighted average % lead.

LOCATIONS

CLEVELAND HEADQUARTERS

BIRMINGHAM DISTRIBUTION CENTER

220 Oxmoor Court. Birmingham, AL 35209

DALLAS DISTRIBUTION CENTER One Merit Drive/PO Box 43127. Cleveland, OH 44143 10614 King William Drive. Dallas, TX 75220

> LONG BEACH PIPE DEPOT 2396 E. Artesia Blvd. Long Beach, CA 90805

SPARKS DISTRIBUTION CENTER 200 Vista Boulevard Suite #106. Sparks, NV 89434

HOUSTON DISTRIBUTION CENTER 4680 S. Sam Houston Pkwy W, Suite 120. Houston, TX 77053