

90° Street Elbow **FTG x P**



Job Name	<input type="text"/>
Job Location	<input type="text"/>
P.O.#	<input type="text"/>
Engineer	<input type="text"/>
Contractor	<input type="text"/>
Wholesaler	<input type="text"/>
Merit Associate	<input type="text"/>

StainlessPress® 90° Street Elbow FTG x P is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z11.17, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

90° Street Elbow **FTG x P**

Item Number			Nominal Size (in)	O.D.	Dimensions (in)				Weight lbs
EPDM	HNBR	FKM			A	B	C	D	
MBF041/26GE	MBF041/26GEH	MBF041/26GEF	½"	0.840	1.57	2.95	2.41	1.34	0.24
MBF043/46GE	MBF043/46GEH	MBF043/46GEF	¾"	1.050	1.89	3.27	2.84	1.69	0.33
MBF0416GE	MBF0416GEH	MBF0416GEF	1"	1.315	2.37	3.82	3.40	2.13	0.37
MBF0411/46GE	MBF0411/46GEH	MBF0411/46GEF	1¼"	1.660	2.20	3.80	3.39	1.97	0.57
MBF0411/26GE	MBF0411/26GEH	MBF0411/26GEF	1½"	1.900	2.48	4.21	3.69	2.24	0.77
MBF0426GE	MBF0426GEH	MBF0426GEF	2"	2.375	3.23	5.59	5.00	3.23	1.34

