

Cap	P
	<p>Job Name <input type="text"/></p> <p>Job Location <input type="text"/></p> <p>P.O.# <input type="text"/></p> <p>Engineer <input type="text"/></p> <p>Contractor <input type="text"/></p> <p>Wholesaler <input type="text"/></p> <p>Merit Associate <input type="text"/></p>

StainlessPress® Cap P is available in sizes 1/2" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Cap					P		
Item Number			Nominal Size (in)	O.D.	Dimensions (in)		Weight lbs
EPDM	HNBR	FKM			A	B	
MBF211/26GE	MBF211/26GEH	MBF211/26GEF	1/2"	0.840	0.85	1.68	0.09
MBF213/46GE	MBF213/46GEH	MBF213/46GEF	3/4"	1.050	0.75	1.70	0.13
MBF2116GE	MBF2116GEH	MBF2116GEF	1"	1.315	0.83	1.85	0.18
MBF2111/46GE	MBF2111/46GEH	MBF2111/46GEF	1 1/4"	1.660	0.93	2.11	0.22
MBF2111/26GE	MBF2111/26GEH	MBF2111/26GEF	1 1/2"	1.900	0.95	2.15	0.33
MBF2126GE	MBF2126GEH	MBF2126GEF	2"	2.375	1.10	2.87	0.55

