

Coupling w/o Stop	Px
	Job Name
	Job Location
	P.O.#
	Engineer
	Contractor
	Wholesaler
	Merit Associate

StainlessPress® Coupling w/o Stop P x P is available in sizes 1/2" - 2" with an EPDM, HNBR or FKM sealing element.

- FIRST TO MARKET Visual Indicator Press Ring[®] (VIPR[®]) facilitates immediate identification of un-pressed connections.
- Mates with IPS (Iron Pipe Size) 304 & 316 Schedule 5 or 10 Stainless Steel Pipe.
- Leak Before Press (LBP) in addition to the VIPR[®], all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- Applications: HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters

- Operating Pressure: from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- Temperature Range: EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Coupling w/o Stop					P x P			
Item Number		Nominal		Dimensions (in)		Weight		
EPDM	HNBR	FKM	Size (in) O.D.	Α	В	lbs		
MBF021/26GE	MBF021/26GEH	MBF021/26GEF	1/2"	0.840	0.83	2.95	0.18	
MBF023/46GE	MBF023/46GEH	MBF023/46GEF	3⁄4"	1.050	0.95	3.40	0.25	
MBF0216GE	MBF0216GEH	MBF0216GEF	1''	1.315	1.02	3.83	0.34	
MBF0211/46GE	MBF0211/46GEH	MBF0211/46GEF	11⁄4"	1.660	1.18	4.49	0.46	
MBF0211/26GE	MBF0211/26GEH	MBF0211/26GEF	11/2"	1.900	1.20	4.81	0.63	
MBF0226GE	MBF0226GEH	MBF0226GEF	2"	2.375	1.77	6.76	1.13	

