

Transition Adapter	P x Groove
	Job Name <input type="text"/> <input type="text"/>
	Job Location <input type="text"/> <input type="text"/>
	P.O.# <input type="text"/> <input type="text"/>
	Engineer <input type="text"/> <input type="text"/>
	Contractor <input type="text"/> <input type="text"/>
	Wholesaler <input type="text"/> <input type="text"/>
Merit Associate <input type="text"/> <input type="text"/>	

StainlessPress® Transition Adapter P x Groove is available in sizes ¾" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Transition Adapter			P x Groove					
Item Number	Nominal Size (in)	O.D.	Dimensions (in)					Weight lbs
			A	B	C	D	E	
MBF433/46GT	¾"	1.050	0.625	0.280	0.938	1.57	4.94	0.25
MBF4316GT	1"	1.315	0.625	0.280	1.190	1.18	5.02	0.34
MBF4311/46GE	1¼"	1.660	0.625	0.280	1.540	1.57	5.12	0.67
MBF4311/26GT	1½"	1.900	0.625	0.280	1.775	1.57	5.20	0.63
MBF4326GT	2"	2.375	0.625	0.340	2.250	2.36	5.77	1.13

