

Van Stone Flange Adapter	P x Flange
	Job Name <input type="text"/> <input type="text"/>
	Job Location <input type="text"/> <input type="text"/>
	P.O.# <input type="text"/> <input type="text"/>
	Engineer <input type="text"/> <input type="text"/>
	Contractor <input type="text"/> <input type="text"/>
	Wholesaler <input type="text"/> <input type="text"/>
Merit Associate <input type="text"/> <input type="text"/>	

StainlessPress® Van Stone Flange Adapter P x Flange is available in sizes ½" – 2" with an EPDM, HNBR or FKM sealing element.

- **FIRST TO MARKET Visual Indicator Press Ring® (VIPR®)** - facilitates immediate identification of un-pressed connections.
- **Mates with IPS (Iron Pipe Size)** 304 & 316 Schedule 5 or 10 Stainless Steel Pipe.
- **Leak Before Press (LBP)** - in addition to the VIPR®, all sizes have leak before press technology, which guarantees a visual indication if the fitting is not pressed.
- **Applications:** HVAC, plumbing, municipal, mechanical, industrial and marine applications.

StainlessPress® Operational Parameters

- **Operating Pressure:** from full vacuum to 300 PSI on Schedule 5 or 10 Stainless Steel Pipe.
- **Temperature Range:** EPDM: -4°F to 230°F. | HNBR: -31°F to 248°F. | FKM: -4°F to 356°F.

StainlessPress® Certifications

IAPMO/ANSI/CAN Z1117, NSF/ANSI/CAN 61 (EPDM only), NSF/ANSI/CAN 372 (EPDM only), FM 1920, American Bureau of Shipping Product Design Assessment (PDA) Certificate 1-5-PR1438892-PDA, Piping System and Couplings.

StainlessPress® Codes and Standards

ASME B31.1, B31.3, B31.9, IPC, IMC, IRC, UPC, UMC, CPC & CMC, City of Los Angeles Plumbing & Mechanical Codes, Massachusetts Regulation 248 CMR 10.00: Uniform State Plumbing Code: Massachusetts State Building Code 780 CMR Ninth edition: Chapter 28: NPSC, NPCC.

Van Stone Flange Adapter					P x Flange								
Item Number			Nominal Size (in)	O.D.	Dimensions (in)								Weight lbs
EPDM	HNBR	FKM			D	k	b	d ₁	d ₂	h	n*	z	
MBF441/26GE	MBF441/26GEH	MBF441/26GEF	½"	0.840	3.54	2.37	0.38	1.38	0.62	3.07	4	2.23	0.95
MBF443/46GE	MBF443/46GEH	MBF443/46GEF	¾"	1.050	3.94	2.75	0.44	1.69	0.62	3.19	4	2.24	1.39
MBF4416GE	MBF4416GEH	MBF4416GEF	1"	1.315	4.25	3.13	0.50	2.00	0.62	3.27	4	2.24	1.84
MBF4411/46GE	MBF4411/46GEH	MBF4411/46GEF	1¼"	1.660	4.53	3.50	0.56	2.50	0.62	3.47	4	2.28	2.40
MBF4411/26GE	MBF4411/26GEH	MBF4411/26GEF	1½"	1.900	4.92	3.87	0.63	2.87	0.62	3.44	4	2.24	2.98
MBF4426GE	MBF4426GEH	MBF4426GEF	2"	2.375	5.91	4.75	0.69	3.63	0.75	4.53	4	2.76	4.79

n* = number of such. Ø d₂ Flange material is AISI 304 and the body is AISI 316

